




THIS IS A TRIANGULATION REFERENCE POINT  
 MEASURE TO THE CENTER OF YOUR FOOTINGS  
 FROM THESE POINTS. REFERENCE WWW.DECKS.COM/DECKBUILDING  
 FOR MORE INFORMATION

THESE PLANS ARE PROPERTY OF DECKS.COM LLC. THE REPRODUCTION OR RESALE OF THESE PLANS IS FORBIDDEN WITHOUT EXPRESSED WRITTEN PERMISSION FROM DECKS.COM LLC.

DISCLAIMER: USE ONLY 2,500 PSI CONCRETE  
 FOR FROST FOOTING FOUNDATIONS

DISCLAIMER: ALL DECK PLANS MUST BE VERIFIED TO ENSURE ACCURACY, COMPLIANCE WITH ALL APPLICABLE STATUTES AND REGULATION AND FITNESS FOR PURPOSES PRIOR TO CONSTRUCTION.



-  12" DIAMETER FOOTING
-  16" DIAMETER FOOTING
-  22" DIAMETER FOOTING

FOOTINGS TO BE INSTALLED TO PROPER DEPTH AS IS REQUIRED BY YOUR LOCAL BUILDING ORDINANCE  
 FROST FOOTINGS SIZES BASED ON 55 LB PER SQUARE FOOT TRIBUTARY LOADS APPLIED TO 1500 PSI SOIL COMPRESSION CAPACITY  
 SEE FOOTING DETAIL

3

FOOTING LAYOUT  
 DECK PLAN 3LSR044  
 REVERSE

© DECKS.COM LLC

ATTENTION: THIS PLAN IS NOT CONSIDERED VALID UNLESS APPROVED BY YOUR LOCAL BUILDING INSPECTOR, ARCHITECT, OR STRUCTURAL ENGINEER.